


<b>ATEXOR code</b>	<b>SFL2LED</b>
<b>Product description</b>	Explosion protected luminary for fixed use
<b>ATEX marking</b>	 Ex II 2 G Ex e mb op is IIC T4 Gb Ex II 2 D Ex tb op is IIIC T90°C Db
<b>Temperature classification</b>	T4 (internal) T90°C (external)
<b>Operating temperature</b>	-40°C ... +40°C
<b>Light source</b>	2 Led module with SafeEye® technology
<b>Light emitted at source</b>	5368 lm
<b>Luminous flux (measured)</b>	3049 lm
<b>Colour temperature</b>	4600 - 5700 K
<b>Colour rendering index</b>	>80
<b>Photobiological safety</b>	Exempt group (No marking required, safe in normal use)
<b>Supply Voltage</b>	230VAC/DC +/- 6%, 50/60Hz
<b>Supply Current (typical)</b>	230V-0,2A
<b>Electrical class</b>	Class 1 (230 VAC)
<b>Power</b>	< 50 W
<b>Cable</b>	MCMK 2x2,5/2,5 or equivalent for fixed use
<b>Cable gland</b>	M25 (for 10-17mm ø cable), installed with cable.
<b>Plug and socket</b>	Not applicable
<b>Enclosure</b>	Dissipative materials (PC & TPE)
<b>Ingress protection</b>	IP66
<b>IK class</b>	08
<b>Weight (without cable and fixings)</b>	3,4 kg
<b>Accessories</b>	70905 ceiling fixing 70904 pole fixing



Product model	Dimensions / mm	
	L	Ø
SLAM FIXED® Linear 2LED WS	1020	115

